



**RainTracker™
VEHICLE INTERFACE
WIRING DIAGRAM**

© 2004 OPTO-ELECTRONIC DESIGN, INC

HOT SIDE SWITCHING
WIPERS RUN WHEN 12V APPLIED TO WIPER MOTOR SLOW OR FAST TERMINALS. MOTOR COMMON AT GROUND.

Ground BLK

+12v GRN

Slow GRN/YEL

Fast BLU/WHT

1.25 YL 1.25 YB 1.25 YR 1.25 YG 1.25 YLW 1.25 YLB 1.25 YLW 1.25 YLB

1.25 LW 1.25 GW 1.25 RB 1.25 YL 1.25 Y 1.25 G 1.25 YB

Front wiper motor

1.25 Y 1.25 YB 1.25 YB

Washer motor

1.25 G

Combination meter

Car speed sensor

F11

F52

F51

R3

F52

3 W

3 L

1.25 G

1.25 B

0.5 G

0.85 R

0.5 W

3 W

3 L

Ignition switch

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Battery

0.5 G

0.85 R

0.5 W

3 W

3 L

Fusible link

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Fuse box

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Mist switch & washer switch

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Wiper select switch

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Intermittent wiper unit

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L

Wiper switch

1.25 G

0.5 G

0.85 R

0.5 W

3 W

3 L